


# DECLARATION OF PERFORMANCE

1307WTGLV01

(glazed wall tiles)




1.	Unique identification code of the product type	Dry pressed ceramic tiles with water absorption $E_b \geq 10\%$	
2.	Type	Dry pressed ceramic tiles with water absorption $E_b \geq 10\%$ Item codes starting with A, B0*, B3, B6, B8, BM, G, H, N, P, Q, S, X02, X07, XK2, XK7, XM2, XM7, XP2, XP7 (* except B04030 and B04070)	
3.	Intended use, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer	For internal walls	
4.	Name and contact address of the manufacturer	Dutch Tiles B.V. Robert Schumandomein 4 6229 ES Maastricht THE NETHERLANDS	
6.	System of assessment and verification of constancy of performance (AVCP)	System 4	
7.	In case of DoP concerning a construction product covered by a harmonized standard	N.A.	
9.	Declared performance		
	<b>Essential characteristics</b>	<b>Performance</b>	<b>Harmonized technical specification</b>
	Reaction to fire	A1n/A1	Based on the decision 96 / 603 / CE and its changes
	Release of dangerous substance, for: - Cadmium* - Lead*	NPD NPD	
	Breaking strength, thickness $\geq 7.5$ mm	> 600 N	EN 14411: 2012
	Breaking strength, thickness < 7.5 mm	> 200 N	
	Slipperiness**	NPD	
	Tactility***	NPD	
	Bond strength/adhesion, for: Cementitious adhesive, type C2	NPD	
	Thermal shock resistance	pass	
	Durability for: - internal use: - external use: freeze-thaw resistance	pass NPD	
	* Only necessary in the case of materials that come into contact with foodstuffs or when required by corresponding national statutory regulations		
	** Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information in our catalogue and technical specification.		
	*** Only for tactile floorings, meaning if requested for blind and visually impaired: as a description of the surface		
10.	Maastricht Airport, 18 <sup>th</sup> June 2013		Signed:   E. Frijns - Managing Director

# DECLARATION OF PERFORMANCE

1307VTGLV01

(glazed floor tiles)




1.	Unique identification code of the product type	Dry pressed ceramic tiles with water absorption $E_b \leq 3\%$	
2.	Type	Dry pressed ceramic tiles with water absorption $E_b \leq 3\%$ Item codes starting with B040, B4, BU, D, J, L, MD, ME, MY, Y0, YK	
3.	Intended use, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer	For internal walls and floorings	
4.	Name and contact address of the manufacturer	Dutch Tiles B.V. Robert Schumandomein 6229 ES Maastricht Airport THE NETHERLANDS	
6.	System of assessment and verification of constancy of performance (AVCP)	System 4	
7.	In case of DoP concerning a construction product covered by a harmonized standard	N.A.	
9.	Declared performance		
	<b>Essential characteristics</b>	<b>Performance</b>	<b>Harmonized technical specification</b>
	Reaction to fire	A1n/A1	Based on the decision 96 / 603 / CE and its changes
	Release of dangerous substance, for: - Cadmium* - Lead*	NPD NPD	
	Breaking strength, thickness $\geq 7.5$ mm	> 700 N	EN 14411: 2012
	Breaking strength, thickness < 7.5 mm	> 1100 N	
	Slipperiness**	NPD	
	Tactility***	NPD	
	Bond strength/adhesion, for: Cementitious adhesive, type C2	NPD	
	Thermal shock resistance	pass	
	Durability for: - internal use: - external use: freeze-thaw resistance	pass NPD	
	* Only necessary in the case of materials that come into contact with foodstuffs or when required by corresponding national statutory regulations		
	** Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information in our catalogue and technical specification.		
	*** Only for tactile floorings, meaning if requested for blind and visually impaired: as a description of the surface		
10.	Maastricht Airport, 18 <sup>th</sup> June 2013		Signed:   E. Frijns - Managing Director

# DECLARATION OF PERFORMANCE

1307VTUGLV01

(unglazed floor tiles)



1.	Unique identification code of the product type	Dry pressed ceramic tiles with water absorption $E_b \leq 0.5\%$	
2.	Type	Dry pressed ceramic tiles with water absorption $E_b \leq 0.5\%$ Item codes starting with BK, MA, MB, MC, MK, MX, KK, XK4, YU, DU	
3.	Intended use, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer	For internal and external walls and floorings	
4.	Name and contact address of the manufacturer	Dutch Tiles B.V. Robert Schumandomein 6229 ES Maastricht Airport THE NETHERLANDS	
6.	System of assessment and verification of constancy of performance (AVCP)	System 4	
7.	In case of DoP concerning a construction product covered by a harmonized standard	N.A.	
9.	Declared performance		
	<b>Essential characteristics</b>	<b>Performance</b>	<b>Harmonized technical specification</b>
	Reaction to fire	A1n/A1	Based on the decision 96 / 603 / CE and its changes
	Release of dangerous substance, for: - Cadmium* - Lead*	NPD NPD	
	Breaking strength, thickness $\geq 7.5$ mm	> 1300 N	EN 14411: 2012
	Breaking strength, thickness < 7.5 mm	> 700 N	
	Slipperiness**	NPD	
	Tactility***	NPD	
	Bond strength/adhesion, for: Cementitious adhesive, type C2	NPD	
	Thermal shock resistance	pass	
	Durability for: - internal use: - external use: freeze-thaw resistance	pass pass	
	* Only necessary in the case of materials that come into contact with foodstuffs or when required by corresponding national statutory regulations		
	** Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information in our catalogue and technical specification.		
	*** Only for tactile floorings, meaning if requested for blind and visually impaired: as a description of the surface		
10.	<p>The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</p> <p>Maastricht Airport, 18<sup>th</sup> june 2013</p> <p>Signed: </p> <p>E. Frijns - Managing Director</p>		